

Product Code	Series	Colour	Gauge	Construction
SF DR 15 PS	SOLAR CONTROL	DUAL REFLECTIVE 15	50µ (2Mil)	3PLY

Performance Fenestration Data

Visible Light Transmission	13%	Glare Reduction	88%
Visible Light Reflection (Internal)	25%	Solar Heat Gain Rejection	76%
Visible Light Reflection (External)	50%	Total Solar Energy Rejected	80%
Solar Energy Transmission	10%	Shading Coefficient	.25
Solar Energy Absorption	38%	Solar Heat Gain Coefficient (g value)	.21
Solar Energy Reflected	52%		
Ultraviolet Rejection	>99%	U-Factor	1.08
		Emissivity	.77

A patented superior scratch resistant coating is featured on all Solartek Window Films

High efficiency for the most demanding environments

For the most effective solar heat rejection in both commercial and residential applications Solartek Dual Reflective Window Films sets the industry standard
 Designed for challenging environments where a high level of solar control is needed without compromising the appearance of a building

Key Features & Benefits	Solar Control Window Films
Reduces Heat Gain – Reduces Energy Usage Reduces Eye Strain – Increases Comfort Levels Protects Against Fading – Blocks UV Rays Increases Visual Privacy Visual Enhancement – Improves Aesthetics	Suitable for application to windows, partition glazing, glazed exteriors, structural glazing, curtain walling, roof-lights and atrium glazing to effectively and economically reduce the problems associated with solar heat gain and visible glare There are a variety of grades available offering different performances and colour choices to best meet your needs

Dual Reflective

One of the most powerful and popular solar heat rejecting films on the market ideal when maximum solar energy rejection is required
 Dual Reflective Films are an excellent choice providing unsurpassed solar performance together with high levels of visible glare reduction