



SF WH MT 75 PS

WHITE MATTE FROST OBSCURE

Film Construction

Ply 2

Mil Thickness 2 (50micron)
Colour: WHITE MATTE

Performance Specification

i ciroimanee specification	
Solar Energy Transmitted	61%
Solar Energy Absorbed	31%
Solar Energy Reflected	8%
Visible Light Transmission	77%
Visible Light Reflected	9%
Ultraviolet Rejected	99%
Solar Heat Gain Coefficient ('g' value)	.66
Shading Coefficient	.81
Glare Reduction	14%
Solar Heat Gain Rejection	19%
Total Solar Energy Rejected	30%

Speciality Series

Other window films in the Speciality Series include Black-Out window film and White/Black Black-Out window film for the highest level of privacy

Also in Bronze, Grey and Silver Matte window films when privacy is desired without blocking light

Countless application possibilities and strong factory back warranty coverage



Product Code:

SF WH MT 75 PS

A patented superior scratch resistant coating is featured on all Solartek Films Speciality Series Window Films

Key Features

Reduces Solar Energy Heat Gain Reduces Visible Glare Reduces UV Radiation Reduces Light Transmission

Key Benefits

Reduces Heat Gain – Reduces Energy Usage Reduces Eye Strain – Increases Comfort Levels Protects Against Fading – Blocks UV Rays Increases Visual Privacy Visual Enhancement – Improves Aesthetics

Unique Products for Specialised Applications

Solartek Films distributes a full line of Speciality window films for a wide range of applications and unique needs

These include coloured, decorative and textured films created to address specific environmental challenges, usually in commercial applications such as privacy, decoration and heat control

Applications

Suitable for application to Windows, Glazed Partitions, Glass Exteriors, Structural Glazing, Curtain Walling, Roof-lights and Atrium Roofs efficiently and economically reducing solar energy loading

Product Warranty

Warranty is subject to window films applied to glass when fitted by an authorised installer in accordance with the manufacturer's recommendations

Performance results are subject to variation within industry standards and are only intended for estimating purposes

Data is representative of actual window film product production

Values are as applied to clear float glass as determined by the manufacturers and independent testing laboratories

Solartek Films Ltd

M25 Business Centre, 121 Brooker Road, Waltham Abbey, Essex EN9 1JH Tel: 08000 15 18 15 Fax: 01920 464488 Email: enquiries@solartekfilms.com