

AFTERCARE

OF SOLARTEK WINDOW TREATMENT

DURING THE FIRST WEEKS FOLLOWING FITTING:

It takes 4 weeks for the film to bond securely to the glass.

If necessary, detergent streaks can be gently removed with water and soft cloth or paper towel.

FILM SHOULD NOT BE CLEANED DURING THIS TIME

GENERAL AFTERCARE:

Cleaning should be done with a squeegee.

A chamois leather should not be used under any circumstances, as it holds grit and acts like sandpaper, whether on film or on glass.

Clean with detergent (washing up liquid) and water.

In very dirty or smoky atmospheres, add a small amount of methylated spirits to the solution.

It is inadvisable to use adhesive tape to attach notices to windows treated with window film. Do not apply paint, artificial snow or adhesive decorations to film surfaces as their removal will damage the film surface.

WARRANTY:

Utmost care is taken to ensure the cleanliness of all surfaces prior to the application of the film and all installations are carried out by our own trained installers.

Solartek will guarantee the works against the film cracking, peeling and/or delaminating for a period of 10 years for internal applications and 3 or 5 years for external applications*.

Please check with Solartek the warranty period of the type of film you require. If at any stage one of the aforementioned happens, Solartek will guarantee that all costs are met by themselves to remove the film and replace it.

*Subject to aftercare and cleaning instructions being strictly followed.

Please note that external applications can only be carried out on a dry, wind-free day



COMPANY REG NO. 4234600



WARNING

NEVER USE AMMONIA-BASED PRODUCTS, VINEGAR OR ANY ABRASIVE MATERIALS.

DO NOT USE A BLOW TORCH ON SURROUNDING PAINT WORK.



SOLARTEK FILMS LTD

42b High Street
Ware, Hertfordshire
SG12 9BY

INFO@SOLARTEKFILMS.COM



CALL NOW

02071 83 55 63

FREEPHONE

08000 15 18 15

WWW.SOLARTEKFILMS.COM