





SOLARTEK

Films

# Solving Glass Related Issues

## SOLARTEK'S SILVER RANGE

Solartek's Silver range is available in a Dark, Medium and Light grades.

- Designed for maximum heat rejection, Solartek Silver is a perfect solution for commercial buildings that receive an excessive amount of solar exposure. Its aluminium, metallized construction provides the comfort and protection needed while reducing the suns glare that causes unwelcome eyestrain.
- Additionally Solartek Silver films will assist with balancing interior hot spots and deliver cost-efficient energy savings for Building Manager's and homeowners whilst giving daylight privacy deterring opportunist burglar's making it difficult to see through your glass that would normally present a view of your expensive belongings.
- With a modern metallic finish Solartek Silver blends in well with factory tinted glass along with today's more sophisticated commercial and residential architecture.
- Aesthetically enhances any coloured brick buildings and looks great against white or grey window frames.

- Blocks 99% UV rays which are extremely harmful.
- Reduces fading.
- 10 year manufacturer's backed warranty when installed by Solartek.
- Scratch Resistant Coating.

Dark	Medium	Light
Heat Reduction 79%	Heat Reduction 65%	Heat Reduction 55%
Glare Reduction 84%	Glare Reduction 64%	Glare Reduction 48%

# SOLARTEK SILVER REFLECTIVE - HIGH



Performance Data			0%	20%	40%	60%	80%	100%
		== = = = /	:	:	:	:	:	:
Total Solar Energy Rejection		78.3%						
Total Solar Absorption		45.5%				•	•	
Total Solar Reflection		44.1%				•	•	
Total Solar Transmission		10.4%				•	•	•
Visible Light Transmission		14.5%						
Visible Light Reflection		55.9%			•		•	
Ultraviolet Light Rejection	Up to	99%						
	•							
Visible Glare Reduction		83.5%						•
Shading Coefficient		0.25						

"U" Factor	0.90
Emissivity	0.61

% may slightly change depending on glass type.

Film Colour: High Reflective Silver

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- High performing and most widely used solar control film. Offers daytime privacy, screening out unsightly areas. Gives an external mirrored appearance to glazing.
- Reduces high levels of incoming solar heat and glare, which makes it suitable for office situations where VDU's are operated.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.
- Also available in external version with 3 year warranty.

## SOLARTEK SILVER REFLECTIVE - MEDIUM

T		t
	TR	
		HE
375-		<b>MI</b>

Performance Data		0%	20%	40%	60%	80%	100%
Total Solar Energy Rejection	65.2%					•	
Total Solar Absorption	46.1%						
Total Solar Reflection	30.9%					•	
Total Solar Transmission	23.0%					•	
						•	
Visible Light Transmission	31.9%						
Visible Light Reflection	37.0%					•	:
		•	•	• • •	•	* * *	•
Ultraviolet Light Rejection U	pto 99%						
		•	•	•		•	
Visible Glare Reduction	63.8%						
Shading Coefficient	0.40			_			

"U" Factor	0.92
Emissivity	0.64

% may slightly change depending on glass type.

Film Colour: Medium Reflective Silver

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- Ideal for office, factory and most commercial applications. Offers excellent solar protection without substantially reducing incoming light.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.
- Also available in an external version with a 3 year warranty.

# SOLARTEK SILVER REFLECTIVE - LOW



Performance Data		0%	20%	40%	60%	80%	100%
Total Solar Energy Rejection	55.0%	:	:			:	:
	38.0%	•	:			•	
Total Solar Absorption					•		
Total Solar Reflection	29.0%						
Total Solar Transmission	33.0%						
Visible Light Transmission	46.0%						
Visible Light Reflection	27.0%			•			
Ultraviolet Light Rejection	95.0%						
Visible Glare Reduction	47.72%				6 6 6	•	•
Shading Coefficient	0.50						

"U" Factor	
Emissivity	

% may slightly change depending on glass type.

Film Colour: Light Silver



Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

## SOLARTEK'S BRONZE RANGE

Solartek's Bronze range is available in a Dark, Medium and Light grades.

- Designed for maximum heat rejection, Solartek Bronze is a perfect solution for commercial buildings that receive an excessive amount of solar exposure. Its aluminium, metallized construction provides the comfort and protection needed while reducing the suns glare that causes unwelcome eyestrain.
- Additionally Solartek Bronze films will assist with balancing interior hot spots and deliver cost-efficient energy savings for Building Manager's and homeowners whilst giving daylight privacy deterring opportunist burglar's making it difficult to see through your glass that would normally present a view of your expensive belongings.
- With a modern metallic finish Solartek Bronze blends in well with factory tinted glass along with today's more sophisticated commercial and residential architecture.
- Aesthetically enhances bronze and brown coloured brick buildings and looks great against brown window frames.

- Blocks 99% UV rays which are extremely harmful.
- Reduces fading.
- 10 Year manufacturer's backed warranty when installed by Solartek.
- Scratch Resistant Coating.

Dark	Medium	Light
Heat Reduction 79%	Heat Reduction 66%	Heat Reduction 57%
Glare Reduction 75.1%	Glare Reduction 58%	Glare Reduction 46%

## SOLARTEK DARK SOLAR BRONZE

Performance Data		0%	20%	40%	60%	80%	100%
		:	:	:	:	:	:
Total Solar Energy Rejection	78.3%						:
Total Solar Absorption	48.6%				•		•
Total Solar Reflection	42.6%					:	
Total Solar Transmission	8.8%			•	• • •	•	
Visible Light Transmission	17.5%				•		
Visible Light Reflection	37.3%						
Ultraviolet Light Rejection	Up to 99%						
Visible Glare Reduction	75.1%						
Shading Coefficient	0.25						

"U" Factor

Emissivity

% may slightly change depending on glass type.

Film Colour: Dark Bronze

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- Excellent solar heat and glare reduction creating a more comfortable environment.
- Allows a more acceptable level of natural light and gives a warm copper tint to glazing.
- Ideal for both commercial and domestic applications.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

## SOLARTEK MEDIUM SOLAR BRONZE

Performance Data		0%	20%	40%	60%	80%	100%
		:	:	6 •	•	:	:
Total Solar Energy Rejection	66.1%		:				
Total Solar Absorption	46.7%						•
Total Solar Reflection	31.1%				•		
Total Solar Transmission	22.2%				• • •	6 6 6	•
Visible Light Transmission	37.0%					• • • •	
Visible Light Reflection	24.5%			•	•	•	
Ultraviolet Light Rejection	Up to 99%						
Visible Glare Reduction	58.0%					•	•
Shading Coefficient	0.39						

"U" Factor	
Emissivity	

% may slightly change depending on glass type.

Film Colour: Medium Bronze

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- Excellent solar heat and glare reduction creating a more comfortable environment.
- Allows a more acceptable level of natural light and gives a warm copper tint to glazing.
- Ideal for both commercial and domestic applications.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

# SOLARTEK LIGHT SOLAR BRONZE

Performance Data			0%	20%	40%	60%	80%	100%
			:	:	:	:	:	:
Total Solar Energy Rejection	56.5	5%		:			•	
Total Solar Absorption	45.5	5%					•	•
Total Solar Reflection	22.8	8%			6 6 6	•	•	
Total Solar Transmission	31.7	%				• • •	•	
						•	•	:
Visible Light Transmission	48.2	.%						:
Visible Light Reflection	17.5	%						:
				:	•	•	•	:
Ultraviolet Light Rejection	Up to 99%	b						
Visible Glare Reduction	45.3	80%						
Shading Coefficient	0.50	)	•	•	•	•	•	•

"U" Factor

Emissivity

% may slightly change depending on glass type.

Film Colour: Light Bronze

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- Good solar heat rejection without sacrificing incoming visible light.
- Gives subtle light bronze colour to glazing, without substantially altering the external appearance of a building.
- Blocks out up to 99% of Ultra Violet light, helping to protect fabrics and furnishings.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

## SOLARTEK'S NEUTRAL RANGE

Solartek's Neutral range is available in a Dark, Medium and Light grades.

- Solartek's Neutral range of Window Film is one of the most popular on the commercial and residential market today.
- It has been designed to blend in well with any interior décor and not to interfere with the natural views outside the window.
- When applied it is less apparent as it does not give a mirrored finish it simply tints the glass whilst still rejecting heat and glare.
- They protect interior furnishing by cutting out 99% of the harmful Ultra Violet rays reducing the risk of fading on all your belongings including expensive paintings, carpets, curtains and furniture.
- This range along with our Ultra Performance range make up 90% of the installations we carry out on glass conservatory roofs throughout the United Kingdom and Europe.

- Not mirrored finish just tinted.
- Cuts out 99% UV.
- Reduces Fading.
- 10 Year manufacturer's backed warranty when installed by Solartek.
- Scratch Resistant Coating.

Dark	Medium	Light
Heat Reduction 63%	Heat Reduction 58%	Heat Reduction 33%
Glare Reduction 76%	Glare Reduction 66%	Glare Reduction 40%

## SOLARTEK NEUTRAL SHADE - DARK



Performance Data			0%	20%	40%	60%	80%	100%
			:	:	:	:	:	:
Total Solar Energy Rejection		62.6%			:		•	
Total Solar Absorption		52.9%					•	
Total Solar Reflection		23.8%			•		•	
Total Solar Transmission		23.3%			6 6 6	•	• • •	
Visible Light Transmission		21.0%				•	•	
Visible Light Reflection		16.5%				•		
Ultraviolet Light Rejection	Up to	99%						
Visible Glare Reduction		76.1%						
Shading Coefficient		0.43	•	•		•		

"U" Factor	0.97
Emissivity	0.70

% may slightly change depending on glass type.

Film Colour: Dark Neutral Grey

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- High performing solar film which gives a subtle grey tint to the glass without being highly mirrored. Ideal for applications where it is desirable to have a uniformed neutral appearance to a building.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

## SOLARTEK NEUTRAL SHADE - MEDIUM



Performance Data			0%	20%	40%	60%	80%	100%
			:	:	:	:	:	:
Total Solar Energy Rejection		58.2%						
Total Solar Absorption		48.3%						
Total Solar Reflection		23.5%			•			
Total Solar Transmission		28.2%						
Visible Light Transmission		29.9%				•	•	
Visible Light Reflection		17.1%					•	•
Ultraviolet Light Rejection	Up to	99%						
Visible Glare Reduction		66.0%					•	
Shading Coefficient		0.48						-

"U" Factor	0.97
Emissivity	0.70

% may slightly change depending on glass type.

Film Colour: Medium Neutral Grey

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- Offers excellent solar control performance without noticeably altering the external appearance of the glass. Reduces incoming solar heat and glare whilst allowing through a high level of natural light.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

# SOLARTEK NEUTRAL SHADE - LIGHT



Performance Data		0%	20%	40%	60%	80%	100%
		:	:	:	:	:	:
Total Solar Energy Rejection	33.0%				:	•	
Total Solar Absorption	36.6%						
Total Solar Reflection	7.8%			:	:	:	
Total Solar Transmission	55.6%					:	
							:
Visible Light Transmission	53.0%						
Visible Light Reflection	7.5%						
Ultraviolet Light Rejection Up t	o 99%						
Visible Glare Reduction	39.7%				•	•	
Shading Coefficient	0.77	•	•	•	•	•	•

"U" Factor	1.08
Emissivity	0.89

% may slightly change depending on glass type..

Film Colour: Light Neutral Grey

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- Gives a light neutral appearance to glazing. Ideal for application to glass areas where visibility through glass is important. Reduces solar heat and blocks up to 99% of UV light reducing risk of fading to furnishings and fabrics.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

## SOLARTEK'S ULTRA PERFORMANCE RANGE

### Solartek's Ultra Performance range is available in a 35, 50 and 70 grades.

- One of the newly developed High-Tech Solar Control Film offering outstanding solar and UV protection without sacrificing as much incoming natural light as other Solar Films with the equivalent Solar Energy Rejection.
- Compare this range to our Neutral, Bronze and Silver ranges and SEE THE DIFFERENCE in the amount of light transmission whilst reducing similar amounts of solar energy (HEAT).
- Ultra Performance 70 is ideal for High Street Shops as it does not effect the customers being able to see through at the window displays as much as equivalent films and cuts out 43% heat as well as 99% Ultra Violet considerably reducing fading of goods increasing profits.

- Cuts out 99% UV.
- Reduces Fading.
- 10 Year manufacturer's backed warranty when installed by Solartek.
- Scratch Resistant Coating.

Ultra Performance	Ultra Performance	Ultra Performance		
35	50	70		
Heat Reduction 72%	Heat Reduction 61%	Heat Reduction 44%		
Glare Reduction 63%	Glare Reduction 42%	Glare Reduction 21%		

## SOLARTEK ULTRA PERFORMANCE 35

### see the difference

Performance Data		0%	20%	40%	60%	80%	100%
		:	:	•	•	:	:
Total Solar Energy Rejection	72.2%						
Total Solar Absorption	30.5%						
Total Solar Reflection	49.5%					•	
Total Solar Transmission	20.0%				•	• • •	:
Visible Light Transmission	32.5%						
Visible Light Reflection	47.1%						
Ultraviolet Light Rejection U	p to 99%						
			•			•	
Visible Glare Reduction	63.0%						
Shading Coefficient	0.32						

"U" Factor	0.96
Emissivity	0.67

% may slightly change depending on glass type.

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- One of the newly developed high-tech Solartek Control films offering outstanding solar and UV protection without sacrificing as much incoming natural light as the other Solar Films with the equivalent Solar Energy Rejection.
- Compare this to our Neutral Shade Dark, Sunset Bronze 20 and Silver Reflective High and 'SEE THE DIFFERENCE'.
- Ideal for both commercial and domestic applications. Significantly reduces incoming heat and provides excellent fading protection for fabrics and furniture.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

## SOLARTEK ULTRA PERFORMANCE 50

### see the difference

Performance Data		0%	20%	40%	60%	80%	100%
		:	:	•	•	:	:
Total Solar Energy Rejection	60.9%		:				•
Total Solar Absorption	25.2%			•			
Total Solar Reflection	<b>42.1%</b>				•		
Total Solar Transmission	32.7%				•	•	
Visible Light Transmission	51.2%						
Visible Light Reflection	<b>36.</b> 1%						
Ultraviolet Light Rejection	Up to 99%						
Visible Glare Reduction	41.8%				•	•	•
Shading Coefficient	0.45	•	•	•	•	•	

"U" Factor	0.97
Emissivity	0.69

% may slightly change depending on glass type.

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- One of the newly developed high-tech Solartek Control films offering outstanding solar and UV protection without sacrificing as much incoming natural light as the other Solar Films with the equivalent Solar Energy Rejection.
- Compare this to our Neutral Shade Medium, Sunset Bronze 30 and Silver Reflective Medium and 'SEE THE DIFFERENCE'.
- Ideal for both commercial and domestic applications. Significantly reduces incoming heat and provides excellent fading protection for fabrics and furniture.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

## SOLARTEK ULTRA PERFORMANCE 70

### see the difference

Performance Data		0%	20%	40%	60%	80%	100%
	10	:	:	:	:	:	:
Total Solar Energy Rejection	43.5%				•		
Total Solar Absorption	23.0%				•		
Total Solar Reflection	26.7%			* *	* * *		
Total Solar Transmission	50.3%					•	
						•	÷
Visible Light Transmission	69.8%						
Visible Light Reflection	20.2%						:
				•	•		•
Ultraviolet Light Rejection	Up to 99%						
Visible Glare Reduction	20.6%						
Shading Coefficient	0.65	•	•	•	•	•	

"U" Factor	0.98
Emissivity	0.71

% may slightly change depending on glass type.

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- One of the newly developed high-tech Solartek Control films offering outstanding solar and UV protection without sacrificing as much incoming natural light as the other Solar Films with the equivalent Solar Energy Rejection.
- Compare this to our Neutral Shade Light, Sunset Bronze 50 and Silver Reflective Low and 'SEE THE DIFFERENCE'.
- Ideal for both commercial and domestic applications. Significantly reduces incoming heat and provides excellent fading protection for fabrics and furniture.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

# SOLARTEK DM PS2 WHITE MATT



Performance Data		0%	20%	40%	60%	80%	100%
	20.00/	:	:	:	:	:	:
Total Solar Energy Rejection	29.0%						
Total Solar Absorption	19.0%			•			
Total Solar Reflection	18.0%			•	•		
Total Solar Transmission	63.0%					•	
			•				:
Visible Light Transmission	69.0%	•				•	•
Visible Light Reflection	18.0%			6 6 8	•	•	
		•		•	•	•	i
Ultraviolet Light Rejection	88%						:
				•			:
Visible Glare Reduction	21.5%						
Shading Coefficient	0.79	•	•	•	•	•	•

"U" Factor	
Emissivity	0.83

% may slightly change depending on glass type.

Film Colour: White Matt

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- Provides a frosted effect creating privacy from both sides of the glazing whilst still allowing a high transmission of the natural light.
- Ideal for use on partitioning, cloakroom and store areas.
- See movement not detail.
- This product carries a full 10 year manufacturer's warranty when professionally installed.

# SOLARTEK'S STKC02 RANGE

Reduce your CO<sub>2</sub> emissions today with Solartek STKCO<sub>2</sub> film.





Glass with STKC0<sub>2</sub>



Glass with an equivalent solar film



This product has been approved by the **Clinton Climate Initiative** as it is **'practical, measurable and significant'** 

- Virtually clear film that reduces energy use costs and has an excellent heat gain reduction.
- It removes Ultra Violet light, reducing fading of fabrics, furnishings and interiors.
- It is available as CDA adhesive product with low visual distortion and providing good optical clarity.

- Increases profits by by reducing air conditioning costs and fading whilst not requiring additional artificial lighting.
- 15 year warranty for internal use when installed professionally.

### STKC02

Heat Reduction 63% Glare Reduction 23%



## SOLARTEK STKC02 HC - C02 REDUCTION FILM

Performance Data			0%	20%	40%	60%	80%	100%
Total Solar Energy Rejection		63.0%						
Total Solar Absorption								
Total Solar Reflection			:	•		:	:	
Total Solar Transmission			•	6 6 6	• • •	•	•	:
			•			•	•	•
Visible Light Transmission		69.0%						
Visible Light Reflection		9.0%		• • •	• • •	* *	•	
			•	•		•	•	
Ultraviolet Light Rejection	Up to	99%						
Visible Glare Reduction		23.0%				•	•	

#### "U" Factor

Emissivity

% may slightly change depending on glass type.

Film Colour: Virtually clear

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- Virtually clear film that reduces energy use costs and has an excellent heat gain reduction.
- It removes Ultra Violet light, reducing fading of fabrics, furnishings & interiors.
- It is available as CDA adhesive product with low visual distortion and providing good optical clarity.
- Increases profits by by reducing air conditioning costs and fading whilst not requiring additional artificial lighting.
- 10 year warranty for internal use when installed professionally.
- Also available in Bomb Blast version

## SOLARTEK COOLSHADE / POLYCARBONATE FILM

Performance Data		0%	20%	40%	60%	80%	100%
Total Solar Energy Rejection	81.1%	:	:		:		
Total Solar Absorption	41.1%						
Total Solar Reflection	40.5%						
Total Solar Transmission	18.4%				•	•	
			:			•	
Visible Light Transmission	21.1%			•			
Visible Light Reflection	41.6%				•	•	
Visible Light Absorbed	37.3%						
Ultraviolet Light Rejection	100%						
Visible Glare Reduction	76.0%						
Shading Coefficient	0.33	•	•	•	:	·	•

"U" Factor

Emissivity

% may slightly change depending on glass type.

Film Colour: Grey

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- A diffused light grey tint when viewed from below.
- Water and alcohol resistant, very cohesive and extremely durable.
- Coolshade is a patched solar film that can be applied to polycarbonate, GPR and plastic substrates. It consists of a soft UV stabilised metallized film on the underside which gives dramatic reduction in the incoming solar heat by continuously reflecting it away.

COOL

This product carries a full 8 year manufacturer's warranty when professionally installed and 2 years when applied externally.

## SOLARTEK CLEAR 100 MICRON SAFETY FILM

Performance Data		0%	20%	40%	60%	80%	100%
Total Solar Energy Rejection	16.5%				•		
Total Solar Absorption	7.8%						
Total Solar Reflection	12.7%				•		
Total Solar Transmission	79.5%						
Visible Light Transmission	88.4%						
Visible Light Reflection	9.2%						
Ultraviolet Light Rejection	Up to 99%						
Visible Glare Reduction	0.45%						
Shading Coefficient	0.96						

"U" Factor	1.08
Emissivity	0.88

% may slightly change depending on glass type.

Film Colour: Clear

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- Optically clear film which will upgrade existing glass to meet requirements of BS6206 Class B and EN12600 Class 2B.
- Protects personnel and property in the event of accidental or deliberate glass breakage.
- Deters potential burglars by making glass far harder to break through.
- Cuts out 99% UV reducing the risk of goods fading (increasing profit).
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 years Manufacturer's warranty when professionally installed.
- Also available in an external grade film with a 3 year warranty.
- Comes in Combined Solar, contact Solartek for more details.

# SOLARTEK **175 MICRON BOMB FILM**

1.07

0.87



Performance Data			0%	20%	40%	60%	80%	100%
		4.6.50/	:		:	:	:	:
Total Solar Energy Rejection		16.5%						
Total Solar Absorption		7.8%		•	•	•	•	
Total Solar Reflection		12.7%			•	•	•	
Total Solar Transmission		79.5%						
Visible Light Transmission		88.5%						
Visible Light Reflection		9.10%			• • •	•	• • •	
Ultraviolet Light Rejection	Up to	99%		-				
Visible Glare Reduction		0.56%						
Shading Coefficient		0.96						

### Features and Benefits

Optically clear, high grade Safety / Security film.

- As recommended by the 'Home Office' for Bomb Blast Protection.
- Upgrade glass to meet requirements of BS6206 Class A and EN12600 Class 1B.
- Offers high level of protection to both personnel and property in the event of deliberate or accidental breakage, vandalism and attempted burglaries.
- Holds glass together in event of attack or explosion protecting people and property.
- It has Scratch Resistant Coating "SRC" to protect the product and avoid the appearance of scratches during normal handling and cleaning practices.
- This product carries a full 10 years Manufacturer's warranty when professionally installed.
- Also available in combined Solar / Bomb Blast range of Films (contact Solartek for more information and samples).

% may slightly change depending on glass type.

Film Colour: Clear

"U" Factor

Emissivity

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

## SOLARTEK DM PS2 BRONZE MATT

0.83

### see the difference

Performance Data		0%	20%	40%	60%	80%	100%
Total Color Front Dejection	29.0%	:	÷		:		
Total Solar Energy Rejection				•	•		
Total Solar Absorption	19.0%			•	•	•	
Total Solar Reflection	18.0%			• • •	•	•	
Total Solar Transmission	63.0%					•	•
						•	:
Visible Light Transmission	69.0%					•	:
Visible Light Reflection	18.0%		:			•	
		•	:	•	•	•	:
Ultraviolet Light Rejection	88%						
Visible Glare Reduction	21.5%						
Shading Coefficient	0.79					•	

Emissivity

% may slightly change depending on glass type.

Film Colour: Bronze Matt

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **Features and Benefits**

- Provides a frosted effect creating privacy from both sides of the glazing whilst still allowing a high transmission of the natural light.
- Ideal for use on partitioning, cloakroom and store areas.
- See movement not detail.
- This product carries a full 10 year manufacturer's warranty when professionally installed internally.

# SOLARTEK WHITE GLOSS VINYL

### **Specification**

### FACE FILM

Face Film	White
Caliper	90 Microns (+/-10%)
Substance	125gsm(+/-10%)
Recommended Life	3 Years
Shrinkage	<1%

### **ADHESIVE**

Removable Acrylic
Low
Excellent
Plus 5 Degrees
Minus 30 to Plus 120 Degrees
Low
150 g/25mm
400 g/25mm

# SOLARTEK Films

Telephone: 08000 15 18 15 • enquiries@solartekfilms.com

### **RELEASE LINER**

Type of Backing Kraft	Glassine - ss siliconized cal.
Colour	White
Substance	65 gsm(+/-10%)
Caliper	55 Microns (+/-10%)

THINK Y

### **Features and Benefits**

- Gives total privacy.
- Internal & external weatherable.
- Available in Gloss & Matt finishes.
- Available in all colours.
- Can digitally print any picture on to these film types.
- Manufacturer's warranty but vary depending on type.

## SOLARTEK'S MANIFESTATION GRAPHICS

Frosted and coloured graphics for office partitioning, shop front graphics, company logos and advertising.



- Available in a huge range of vinyl and colour combinations, window graphics from Solartek can turn simple glazing systems into eye-catching adverts or images.
- Not only do they enhance the existing glass, but they also satisfy legal requirements to make glass apparent, preventing injury to members of the public and your employees.
- Our design experts are able, through in depth discussions, to take an original concept and transform your glass doors and windows into a high impact form of advertising that will attract extra custom and subsequently increase profit to your business.
- Also available is the latest form of advertising on glass by using digital print on to film (any picture or photo) and applied to your glass.

### What we can offer:

- The latest technology in window film to produce significant energy reduction without the traditional reduction of visible light.
- Individual building model assessment to identify expected reductions in specific buildings.
- Individual building thermal stress analysis.
- EU installation service.
- Available in combined Bomb Blast / Heat Reduction.
- Manufacturer warranty on film quality and performance.

### Other products Solartek supply and install:

- Bomb Blast Protection
- Edge Retention Systems
- Privacy / Frosted Film
- Security Film
- Safety Film
- Workplace (Health, Safety & Welfare) Regulation 14 Glazing Identification Surveys
- Manifestation Graphics
- Conservatory Perspex Heat Reduction Film
- Glare Reduction

# SOLARTEK Films

### Solartek Films Ltd contact details:

Telephone:	08000 15 18 15
Fax:	01920 464 488
Email:	enquiries@solartekfilms.com
Website:	www.solartekfilms.com
Skype name:	Solartek Films Ltd



Solartek Films Ltd Nationwide and European Depots London • Plymouth • Cardiff • Birmingham • Sheffield • Newcastle Glasgow • Belfast • Malaga Spain